



# The 12-Kilo Millennium Coffee Roaster

Patent Pending

**American Made, Hand Built Quality**

## SPECIFICATIONS

12 Kilo Model (30lb) Coffee Roaster. Four roasts per hour. Designed for easy operation, low maintenance, and a long lifetime. Your choice of several standard colors, trim types and finishes.

- Weight: 1350 lbs
- Total Dimensions<sup>1</sup>: 71"x31"x71"(LxWxH)
- Cyclone Exhaust: 6" Cooler Exhaust: 5"<sup>2</sup>
- 10,000—90,000 BTUs adjustable
- Gas Supply: 3/4" Pipe with Natural at 9" w.g. or Propane at 13" w.g.
- Quenching requires a 3/8th inch water line (for applicable models)

[1] Allow 18" clearance minimum for service. Dimensions do not include chaff collector

[2] Use Class A type positive pressure piping

[3] **Special note for Propane or bottled gas.** it is highly recommended for your safety that you purchase a quality propane regulator from a Professional source. You must have the correct regulator for the type of supply that you are connecting the roaster to. Changing supply type can or not having the regulator set to the pressure needs of the roaster or the source can be safety hazard and also damage the roaster. If you have needs for regulator please contact one of our Engineering staff for the correct one.

- |                          |                     |  |
|--------------------------|---------------------|--|
| <input type="checkbox"/> | 12kiloMill Gas      | 3-Phase / 208-240 V / 15mps                                    |
| <input type="checkbox"/> | 12kiloMill Gas      | Single Phase / 208-240 V / 20amps                              |
| <input type="checkbox"/> | 12kiloMill Electric | Single Phase / 208-240 V / 120 amps                            |
| <input type="checkbox"/> | 12kiloMill Electric | 3-Phase / 208-240V / 380V / 480V<br>75amps / 50 amps / 40 amps |

**NEW FOR 2017!** Stainless cooler liner, magnehelic gauges for air flow and gas pressure, digital environmental air temp gauge, and air dampener control at NO CHARGE.

## FRAME

- Heavy-duty stainless steel drum, cooler screen, and cooler liner
- Double insulated housings.
- Easy to service roaster fan and separate fan for cooler
- Removable cooler for easy cleaning with adjustable slip clutch
- Industrial gear drives for smooth operation of drum and cooler stirrer, with no bulky belts or noisy chains.
- Equipped with heavy duty direct drive steel-cooling fan.
- Heavy-duty motors with UL 508-A approved industrial control system and motors, adjustable overloads and contactors.
- Adjustable legs for ease of movement and cleaning
- Easy to adjust housing for the main drum bearing in designed to keep the bearing cooler and lubricated
- Grooved faceplate to seal drum for less product loss
- Water jet and precision milled steel parts made in-house

## OPERATION

- 24 volt operator controls for safe operation.
- Even and accurate heat controls;
- Cast iron rectangular burners with a large venture mixer or industrial electric elements
- Free Standing cyclonic chaff collector.
- Standard lighted push button on-off switches, motor starters and overloads with fault protection.
- Two gas gauges provided for incoming gas pressure and outgoing gauge at gate valve to adjust burner output.
- Profiler model has programmable and digital control
- All models include digital bean probe with controller and alarm and environment temp gauge

**US Roaster Corp**

1530 West Main Street ■ Oklahoma City, OK 73106 ■ Phone: 405.232.1223  
Fax: 405.232.1255 ■ Email: dan@roastersexchange.com



# The 12-Kilo Millennium Coffee Roaster

Patent Pending

**American Made, Hand Built Quality****Models**

- 12-Kilo Stock Model
- 12-Kilo Standard Model
- 12-Kilo Open Frame Model
- 12-Kilo Deluxe Model

**Add-ons**

- Touchscreen Profiler
  - Semi-Automatic
- Fingertip control
- Roast Helper Option

**Touchscreen Profiler Options**

- Large PLC memory for 999 profiles
- Wireless touchscreen to connect to iPhone/iPad
- 10 in color display (6 in mono comes standards)
- Flow meter on water quenching
- Air gates on cooler discharge or green bean hopper

**Additional Options**

- Electric roaster door with override and auto discharge (non PLC)
- Stainless polished cooler

**Additional Options (continued)**

- Smooth or dimensional stainless or hammered copper drum wrap
- Dimensional patterned stainless drum wrap
- Hammered copper cooler wrap
- Pin striping
- Two tone paint
- Clear coat over paint with metal flake
- Maintenance hour meter
- Digital roast timer
- Environmental air temperature with digital read-out
- Automatic quenching for drum or cyclone
- Chrome bean chute
- Chrome face plate
- Bean light (110 V only)
- Install extra bean thermocouple for customers data logger
- Phidget with USB connection and two thermocouples installed
- Drum speed control
- Custom paint color
- Cleaning kit
- Roaster controls on control head
- Magnet in cooler discharge

**About Us.** The U.S. Roaster Corp. is famous for producing the world's finest roasters that create the best roasted coffee. Partnering with specialty coffee roast masters world-wide we have developed a roaster of superior design, unmatched quality, great reliability, and ease of use. Our Millennium line of roasters provide the roast master with unlimited profile capabilities and unparalleled roast quality. By the second crack you will know why the "Quality of the Roast" comes first at U.S. Roaster Corp.

**Free One-on-one training session is provided in Oklahoma City!**

Contact us for information

1530 West Main St.  
Oklahoma City, OK. 73106  
405.232.1223.  
dan@roastersexchange.com  
www.usroastercorp.com

All local codes to be followed on install.

We reserve the right to make changes due to ongoing improvements.

**US Roaster Corp**

1530 West Main Street ■ Oklahoma City, OK 73106 ■ Phone: 405.232.1223  
Fax: 405.232.1255 ■ Email: dan@roastersexchange.com